

### 2000 Series Fert/Lime/Flowable Product Spreaders

- Eight Model Range – 6m<sup>3</sup> to 16.8m<sup>3</sup> (Hopper Level)
- Hydraulic Drive Models Only – No PTO
- ISOBUS Interface, Auto Rate Control, VRA, Load Sense
- Single & Twin Belt Models (Twin Belt Fertiliser Only)
- Auto On/Off, Basic Single Belt or Twin Belt - Section Control
- Weight Cell Option – ISOBUS
- Single & Twin Floor Belt Options
- 12 – 56 mtr Spread Widths
- Standard Incorporated Stainless Steel – Key Areas
- Full Stainless-Steel Hopper Options
- Adjustable Rear Spreading Deck
- ISOBUS Headland Border Control
- Single & Tandem Axle Models
- Hydraulic Folding Wind Boom Lime Deflector Curtains
- Optional Equipment Available



### 1000-2K Series Fert/Lime/Flowable Product Spreaders

- Eight Model Range – 2.6m<sup>3</sup> to 13.9m<sup>3</sup> (Hopper Level)
- Hydraulic Drive & Ground Drive Options – No PTO
- ISOBUS Interface, Auto Rate Control, VRA, Load Sense
- Single Floor Belt Models Only
- Section Control: Auto On/Off or Basic Single Belt SC
- Weight Cell Options – ISOBUS & Read Only
- 12 – 56 mtr Spread Widths
- Incorporated Stainless Steel – Key Areas
- Full Stainless-Steel Hopper Options
- In-Cab & ISOBUS Headland Border Control Options
- Single & Tandem Axle Models
- Hydraulic Folding Wind Boom Lime Deflector Curtains
- Optional Equipment Available



### Pro & Pro+ Series Vertical/Horizontal Manure Spreaders

- Twelve Model Range – 4.6m<sup>3</sup> to 16.9m<sup>3</sup> (Level)
- Hydraulic Floor Drive (Manual/Auto Options)
- Twin Chain Floor System & Quick fit Galvanised Lats
- Hydraulic Slurry Door
- Single & Tandem Axle Models
- Rear Spreading Hood - Option
- ISOBUS Rate Controller - Option
- Sprung Drawbar - Option
- Weight Cells Option
- Wide Angle 1000 PTO, Boron Beaters/Tips
- Air/Hydraulic Brake Options
- Wooden or Steel Extensions
- Dynamically Balanced Vertical/Horizontal Beaters
- Optional Equipment Available



## 2000 Series – Fertiliser, Lime, Gypsum & Bulk Flowable Product Spreaders

Model	AS265	AS285	AS2100	AS2120	AS2130T	AS2150T	AS2200T	AS2220T
Hopper Length (mm)	3330	3630	3630	4228	4640	4640	5640	5640
Hopper Width (mm)	2245	2245	2245	2245	2245	2625	2245	2616
Loading Height including loadcells (mm)	2345	2580	2785	2790	2715	2980	2872	3135
Capacity Hopper Level (m³)	6.0	6.6	8.2	9.7	10.7	13.6	13.0	16.8
Lime Capacity Heaped (kg)	9.2	12.0	13.5	14.5	19	19.5	23.3	25.0
Standard Tyres - 10 stud	650/65R30.5	650/65R30.5	650/65R30.5	650/65R30.5	600/55R26.5	600/55R26.5	650/65R30.5	650/65R30.5
Axle Section (mm)	120 X 120	150 X 150	150 X 150	150 X 150	2 X 127 Rnd	2 x 120 Rnd	2 x 150 Sq	2 x 150 Sq
Dampened Drawbar	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Drive System	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive
Rate Controller Type	ISOBUS	ISOBUS	ISOBUS	ISOBUS	ISOBUS	ISOBUS	ISOBUS	ISOBUS
Section Control - Single Belt Auto On/Off (1 Sec)	Option-fert/lime	Option fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime
Section Control - Single Belt Basic (10 Sec)	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime
Section Control - Twin Belt (14 SECTIONS)	Option-fert only	Option-fert only	Option-fert only	Option-fert only	Option-fert only	Option-fert only	Option-fert only	Option-fert only
Hydraulic Brakes (Air Brake Options)	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

## 1000-2K Series – Fertiliser, Lime, Gypsum & Bulk Flowable Product Spreaders

Model	AS35-2K	AS55-2K	AS65-2K	AS85-2K	AS100-2K	AS120-2K	AS130T-2K	AS150T-2K
Hopper Length (mm)	3000	3000	3600	3600	3600	4223	4624	4624
Hopper Width (mm)	1800	2000	2000	2250	2250	2250	2244	2244
Loading Height (Loads Cells) (mm)	2050	2250	2250	2610	2800	2800	2725	3000
Capacity Hopper Level (m³)	2.6	4.1	4.9	6.8	8.5	9.9	10.8	13.9
Lime Capacity Heaped (kg)	5282	7612	9232	12546	15260	17346	19201	24157
Standard Tyres - 10 Stud	650/55R26.5	650/55R26.5	650/65R30.5	650/65R30.5	650/65R30.5	650/65R30.5	600/55R26.5	600/55R26.5
Axle Section (mm)	120 x 120	120 x 120	120 x 120	150 x 150	150 x 150	150 x 150	2 x 127 Rnd	2 x 127 Rnd
Dampened Drawbar	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Land Drive & Hydraulic Options	Land or Hyd Drive	Land or Hyd Drive	Land or Hyd Drive	Land or Hyd Drive	Land or Hyd Drive	Land or Hyd Drive	Hydraulic Drive	Hydraulic Drive
Rate Controller Type	Land Drive/ ISOBUS	Land Drive/ISOBUS	Land Drive/ISOBUS	Land Drive/ISOBUS	Land Drive/ISOBUS	Land Drive/ISOBUS	ISOBUS	ISOBUS
Section Control Single Belt Auto On/Off (1 Sec)	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime
Section Control Single Belt Basic (10 Section)	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime
Hydraulic Brakes (Air Brake Options)	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

## Pro & Pro+ Series – Vertical (VBS) & Horizontal (HBS) Beater Rear Discharge Manure Spreaders

Series / Model	PRO SERIES						PRO+ SERIES		
	6000 VBS	9000 VBS	10000 VBS	10000- C VBS	11000 VBS	12000 VBS	14000 VBS/HBS	16000 VBS/HBS	18000 VBS/HBS
Capacity Tons	6	9	10	10	11	12	14	16	18
Volume (m³) No Extensions - Level	4.6	7.1	8.1	7.7	8.5	9.8	11.8	13.0	16.9
Volume (m³) No Extensions - Heaped	8.0	10.5	11.5	11.1	11.9	13.2	15.2	16.4	20.3
m³ (225mm Wood Ext.) Level	6.2	9.1	10.5	9.8	10.7	12.2	14.4	15.9	20.1
m³ (225mm Wood Ext.) Heaped	8.1	11.9	13.6	13.0	13.7	15.6	18.2	20.1	25.5
m³ (250mm Wood Ext.) Level	6.3	9.4	10.7	10.0	10.9	12.5	14.7	16.2	20.5
m³ (250mm Wood Ext.) Heaped	8.3	12.1	19.8	13.3	13.9	15.9	18.5	20.4	25.7
m³ (450mm Steel Ext.) Level	7.7	11.2	12.8	11.9	12.8	14.6	17.0	18.8	23.3
m³ (450mm Steel Ext.) Heaped	9.7	13.9	15.9	15.1	15.8	18.0	20.9	23.0	28.6
Wide Angle PTO - RPM	1000	1000	1000	1000	1000	1000	1000	1000	1000
Beater Protection	Shearbolt	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch
Floor Chain & Size	2 x 16mm	2 x 16mm	2 x 16mm	2 x 16mm	2 x 16mm	2 x 16mm	2 x 20mm	2 x 20mm	2 x 20mm
Unladen Weight-Kg	3900	4825	5080	5000	5000	5400	7165	7380	7935
Standard Tyres	520/85 R38	520/85 R38	580/70 R38	580/70 R38	580/70 R38	580/70 R38	580/70 R38	580/70 R38	710/70R42
VBS Boron Tips 12mm - Qty	44	52	60	52	60	60	60	60	60
VBS Rotor Speed-RPM	420	420	420	420	420	420	423	423	423
VBS Rotor Diameter-mm	750	750	750	750	750	750	855	855	855
VBS Rotor Height - mm	1572	1717	1717	1912	1912	1912	2172	2172	2172
VBS Paddle Diameter-mm	2172	780	780	780	780	780	1175	1175	1175
HBS Upper Rotor Dia-mm	n/a	n/a	n/a	n/a	n/a	n/a	510	510	510
HBS Lower Rotor Dia-mm	n/a	n/a	n/a	n/a	n/a	n/a	700	700	700
HBS Paddle Diameter-mm	n/a	n/a	n/a	n/a	n/a	n/a	1090	1090	1090
HBS Flights per Rotor-Qty	n/a	n/a	n/a	n/a	n/a	n/a	18 upper & 18 lower	18 upper & 18 lower	18 upper & 18 lower
HBS Rotor Speeds-RPM	n/a	n/a	n/a	n/a	n/a	n/a	232 upper/316 lower	232 upper/316 lower	232 upper/316 lower
HBS Disks-RPM	n/a	n/a	n/a	n/a	n/a	n/a	506	506	506

### Other Options Available (Range, Model & Specification Dependent) – Discuss with Dealer:

- LOAD CELLS - ISOBUS - TYRE OPTIONS - SALT/SAND KITS- STAINLESS STEEL - RATE CONTROLLERS - REAR BUMPER/DRAWBAR - WORK LIGHTS - EXTENSIONS - HITCH OPTIONS  
- AIR/HYD BRAKES - STEERING AXLE - HYDRAULIC DRIVE - BORDER CONTROL - HYD/ELECTRIC COVERS - MUDGUARDS - LIME BOOMS & CHAINS - FERT/LIME DISKS

 Coolnaha, Ballyhaunis, Co. Mayo, Ireland. F35 Y157  + 353 9496 31808  info@agrispread.com  www.agrispread.com

+ PRECISION SPREADING EQUIPMENT

www.agrispread.com    /agri-spread