

2000 Series Fert/Lime/Flowable Product Spreaders

- Eight Model Range – 212 cu ft to 593 cu ft (Hopper Level)
- Hydraulic Drive Models Only – No PTO
- ISOBUS Interface, Auto Rate Control, VRA, Load Sense
- Single & Twin Belt Models (Twin Belt Fertiliser Only)
- Auto On/Off, Basic Single Belt or Twin Belt - Section Control
- Weight Cell Option – ISOBUS
- Single & Twin Floor Belt Options
- 40 – 158 ft Spread Widths
- Standard Incorporated Stainless Steel – Key Areas
- Full Stainless-Steel Hopper Options
- Adjustable Rear Spreading Deck
- ISOBUS Headland Border Control
- Single & Tandem Axle Models
- Hydraulic Folding Wind Boom Lime Deflector Curtains
- Optional Equipment Available



1000-2K Series Fert/Lime/Flowable Product Spreaders

- Eight Model Range – 91 cu ft to 545 cu ft (Hopper Level)
- Hydraulic Drive & Ground Drive Options – No PTO
- ISOBUS Interface, Auto Rate Control, VRA, Load Sense
- Single Floor Belt Models Only
- Section Control: Auto On/Off or Basic Single Belt SC
- Weight Cell Options – ISOBUS & Read Only
- 40 – 158 ft Spread Widths
- Incorporated Stainless Steel – Key Areas
- Full Stainless-Steel Hopper Options
- In-Cab & ISOBUS Headland Border Control Options
- Single & Tandem Axle Models
- Hydraulic Folding Wind Boom Lime Deflector Curtains
- Optional Equipment Available



Pro & Pro+ Series Vertical/Horizontal Manure Spreaders

- Twelve Model Range – 163 cu ft to 597 cu ft (Level)
- Hydraulic Floor Drive (Manual/Auto Options)
- Twin Chain Floor System & Quick fit Galvanised Lats
- Hydraulic Slurry Door
- Single & Tandem Axle Models
- Rear Spreading Hood - Option
- ISOBUS Rate Controller - Option
- Sprung Drawbar - Option
- Weight Cells Option
- Wide Angle 1000 PTO, Boron Steel Beater Flights & Tips
- Air/Hydraulic Brake Options
- Wooden or Steel Extensions
- Dynamically Balanced Vertical/Horizontal Beaters
- Optional Equipment Available



2000 Series – Fertiliser, Lime, Gypsum & Bulk Flowable Product Spreaders

Model	AS265	AS285	AS2100	AS2120	AS2130T	AS2170T	AS2200T	AS2220T
Hopper Length (ft & in)	10' 10"	11' 11"	11' 11"	13' 10"	15' 3"	15' 3"	18' 6"	18' 6"
Hopper Width (ft & in)	7' 4"	7' 4"	7' 4"	7' 4"	7' 4"	8' 7"	7' 4"	8' 7"
Loading Height including loadcells (ft & in)	7' 8"	8' 6"	9' 2"	9' 2"	8' 11"	10' 3"	9' 5"	10' 3"
Capacity Hopper Level (cu ft)	212	232	289	341	377	535	458	593
Lime Capacity Heaped (lbs)	20,283	26,455	29,762	31,967	41,896	42,990	51,266	55,116
Standard Tyres - 10 stud	650/65R30.5	650/65R30.5	650/65R30.5	650/65R30.5	600/55R26.5	710/50R26.	650/65R30.5	650/65R30.5
Axle Section (mm)	120 X 120	150 X 150	150 X 150	150 X 150	2 X 127 Rnd	2 x 120 Rnd	2 x 150 Sq	2 x 150 Sq
Dampened Drawbar	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Drive System	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive	Hydraulic Drive
Rate Controller Type	ISOBUS	ISOBUS	ISOBUS	ISOBUS	ISOBUS	ISOBUS	ISOBUS	ISOBUS
Section Control - Single Belt Auto On/Off (1 Sec)	Option-fert/lime	Option fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime
Section Control - Single Belt Basic (10 Sec)	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime
Section Control - Twin Belt (14 SECTIONS)	Option-fert only	Option-fert only	Option-fert only	Option-fert only	Option-fert only	Option-fert only	Option-fert only	Option-fert only
Hydraulic Brakes (Air Brake Options)	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

1000-2K Series – Fertiliser, Lime, Gypsum & Bulk Flowable Product Spreaders

Model	AS35-2K	AS55-2K	AS65-2K	AS85-2K	AS100-2K	AS120-2K	AS130T-2K	AS170T-2K
Hopper Length (ft & in)	9' 10"	9' 10"	11' 10"	11' 10"	11' 10"	13' 10"	15' 2"	15' 2"
Hopper Width (ft & in)	5' 11"	6' 7"	6' 7"	7' 5"	7' 5"	7' 5"	7' 4"	7' 4"
Loading Height (Loads Cells) (ft & in)	7"	7' 5"	7' 5"	8' 7"	9' 2"	9' 2"	8' 11"	10' 3"
Capacity Hopper Level (ft & in)	91	144	173	240	300	349	383	545
Lime Capacity Heaped (ft & in)	11,645	16,781	20,352	27,658	33,643	38,241	42,331	57,936
Standard Tyres - 10 Stud	650/55R26.5	650/55R26.5	650/65R30.5	650/65R30.5	650/65R30.5	650/65R30.5	600/55R26.5	600/55R26.5
Axle Section (mm)	120 x 120	120 x 120	120 x 120	150 x 150	150 x 150	150 x 150	2 x 127 Rnd	2 x 127 Rnd
Dampened Drawbar	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Land Drive & Hydraulic Options	Land or Hyd Drive	Land or Hyd Drive	Land or Hyd Drive	Land or Hyd Drive	Land or Hyd Drive	Land or Hyd Drive	Hydraulic Drive	Hydraulic Drive
Rate Controller Type	Land Drive/ ISOBUS	Land Drive/ISOBUS	Land Drive/ISOBUS	Land Drive/ISOBUS	Land Drive/ISOBUS	Land Drive/ISOBUS	ISOBUS	ISOBUS
Section Control Single Belt Auto On/Off (1 Sec)	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime
Section Control Single Belt Basic (10 Section)	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime	Option-fert/lime
Hydraulic Brakes (Air Brake Options)	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

Pro & Pro+ Series – Vertical (VBS) & Horizontal (HBS) Beater Rear Discharge Manure Spreaders

Series / Model	PRO SERIES						PRO+ SERIES		
	6000 VBS	9000 VBS	10000 VBS	100000- C VBS	11000 VBS	12000 VBS	14000 VBS/HBS	16000 VBS/HBS	18000 VBS/HBS
Capacity Tons	6	9	10	10	11	12	14	16	18
Volume (cu ft) No Extensions - Level	163	251	287	273	301	345	11.8	415	457
Volume (cu ft) No Extensions - Heaped	167	254	290	276	305	348	15.2	418	461
cu ft (225mm Wood Ext.) Level	218	323	369	346	376	430	14.4	508	560
cu ft (225mm Wood Ext.) Heaped	287	420	479	460	483	551	18.2	614	709
cu ft (250mm Wood Ext.) Level	224	331	378	354	385	440	14.7	519	571
cu ft (250mm Wood Ext.) Heaped	293	428	488	468	491	560	18.5	654	720
cu ft (450mm Steel Ext.) Level	272	395	451	419	451	516	17.0	602	662
cu ft (450mm Steel Ext.) Heaped	341	492	561	533	558	616	20.9	737	811
Wide Angle PTO - RPM	1000	1000	1000	1000	1000	1000	1000	1000	1000
Beater Protection	Shearbolt	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch	Shearbolt/Clutch
Floor Chain & Size	2 x 16mm	2 x 16mm	2 x 16mm	2 x 16mm	2 x 16mm	2 x 16mm	2 x 20mm	2 x 20mm	2 x 20mm
Unladen Weight-Kg	3900	4825	5080	5000	5000	5400	7165	7380	7935
Standard Tyres	520/85 R38	520/85 R38	580/70 R38	580/70 R38	580/70 R38	580/70 R38	580/70 R38	580/70 R38	710/70R42
VBS Boron Tips 0.47 in - Qty	44	52	60	52	60	60	60	60	60
VBS Rotor Speed-RPM	420	420	420	420	420	420	423	423	423
VBS Rotor Diameter-in	29.52	29.52	29.52	29.52	29.52	29.52	34	34	34
VBS Rotor Height - in	61.88	67.59	67.59	75.27	75.27	75.27	85.51	85.51	85.51
VBS Paddle Diameter-in	30.70	30.70	30.70	30.70	30.70	30.70	46.25	46.25	46.25
HBS Upper Rotor Dia-in	n/a	n/a	n/a	n/a	n/a	n/a	20.07	20.07	20.07
HBS Lower Rotor Dia-in	n/a	n/a	n/a	n/a	n/a	n/a	27.55	27.55	27.55
HBS Paddle Diameter-in	n/a	n/a	n/a	n/a	n/a	n/a	42.91	42.91	42.91
HBS Flights per Rotor-Qty	n/a	n/a	n/a	n/a	n/a	n/a	18 upper & 18 lower	18 upper & 18 lower	18 upper & 18 lower
HBS Rotor Speeds-RPM	n/a	n/a	n/a	n/a	n/a	n/a	232 upper/316 lower	232 upper/316 lower	232 upper/316 lower
HBS Disks-RPM	n/a	n/a	n/a	n/a	n/a	n/a	506	506	506

Other Options Available (Range, Model & Specification Dependent) – Discuss with Dealer:

- LOAD CELLS - ISOBUS - TYRE OPTIONS - SALT/SAND KITS- STAINLESS STEEL - RATE CONTROLLERS - REAR BUMPER/DRAWBAR - WORK LIGHTS - EXTENSIONS - HITCH OPTIONS
- AIR/HYD BRAKES - STEERING AXLE - HYDRAULIC DRIVE - BORDER CONTROL - HYD/ELECTRIC COVERS - MUDGUARDS - LIME BOOMS & CHAINS - FERT/LIME DISKS

16 Spinnaker Way, Unit 17, Concord, Ontario L4K 2T8 | Toll Free 877 361-2821 | @ marketing@reesincw.ca | www.reesincw.ca

+ PRECISION SPREADING EQUIPMENT

www.agrispread.com

